

NAME

`newaliases` – zmailer aliases database rebuilder

SYNOPSIS

`newaliases` [`-s`] [`/file/path`]

DESCRIPTION

This utility has been superseded by `zmailer newdb` mechanism, but can be used in few places, provided that `aliases` type database is being produced with default settings!

Running the `newaliases(1zm)` without parameters rebuilds the `aliases(5zm)` database used by the `router(8zm)` configuration at most sites.

This script wrapper constructs argument list for underlying `newdb(8zm)` program (and `makedb(8zm)` under it,) which does actual `aliases(5zm)` format database compilation work.

OPTIONS

`-s`

Optionally silence the underlying `makedb(8zm)` program.

`/file/path`

Optionally specify file path (fully qualified, or relative) to the database to be compiled.

With this option one can specify which database is to be compiled.

ENVIRONMENT VARIABLES

ZCONFIG

This environment variable is expected to be inherited from the user's environment for cases where default location isn't correct.

Z-ENVIRONMENT VARIABLES

Following *ZENV-variables* are used by the `newaliases(1zm)` program:

MAILVAR

Tells where the ZMailer's runtime databases, etc. are by default.

FILES

`/opt/mail/zmailer.conf` (ZCONFIG)

`/opt/mail/db/aliases` (MAILVAR/db/aliases)

SEE ALSO

`aliases(5zm)`, `router(8zm)`, `makedb(8zm)`, `newdb(8zm)`, `zbases.conf(5zm)`, `zmailer(1zm)`, `zmailer.conf(5zm)`.

AUTHOR

This program authored and copyright by:

Rayan Zachariassen <no address>

Fairly radical rewriting by:

Matti Aarnio <mea@nic.funet.fi>