

**NAME**

manual-expirer – wrapper for *expirer*(8zm) transport agent program

**SYNOPSIS**

```
manual-expirer [-c channel] [-h "hostname"] [-u "user@domain"] [-l logfile] [-sV]
                [-m "message string"]
```

**DESCRIPTION**

The *manual-expirer* is tool for ZMailer administrator for removing mails from the spool by expiring them prematurely.

*manual-expirer* wraps *expirer*(8zm) utility call with suitable parameters for generating input.

Suggested parameters for *expirer*(8zm) are:

- c *channel*  
    Message recipient selector "*channel*" (optional)
- h *hostname*  
    Message recipient selector "*host*" (optional)
- u "*user@domain*"  
    Message recipient selector "*user*" (optional)
- m '*message string*'  
    An alternate report string.
- s  
    Message expiration occurs without any report to anywhere. Silent mode.
- V  
    Print program version, and exit.

**ENVIRONMENT VARIABLES**

The *manual-expirer* program inherits **ZCONFIG** environment variable, and reads it, and uses value of **MAILBIN** in it to locate the *expirer*(8zm) utility, as well as to determine where **POSTFOFFICE**/transport/ directory is located at.

**SEE ALSO**

*scheduler*(8zm), *expirer*(8zm), *zmailer.conf*(5zm).

**AUTHOR**

This script is authored and copyright by:  
Matti Aarnio <mea@nic.funet.fi>